Technical Data

Issue 11 July 2003

AT7 PVC Electrical Insulation Tape

General description

A lead free PVC Electrical Insulation Tape coated with pressure sensitive adhesive.

- Flame retardant.
- Self-extinguishing.
- Easy tear.
- Easy unwind.
- Flexible.
- Conformable to awkward shapes.
- Water resistant.
- Good abrasion resistance.
- UV resistant.
- Non-corrosive adhesive.

Specifications

Certification* to the following standards may be available on request. BS EN 60454/Type 2 (Formerly BS 3924)

Technical data

Thickness 0.13mm

Breaking Load 26 N/cm

Elongation 180%

Adhesion

Steel 2.4 N/cm Self 2.1 N/cm

Water Extract

pH 6.8

Conductivity Max.2 mS/m

Electrical Properties

B/down Voltage 8.0 kV

1 Min Proof Test 6.0 kV

Insulation Resist 10¹¹ ohms

Cu Corrosion No Staining

Flame Retardancy Self extinguishing Service Temp -5°C to $+70^{\circ}\text{C}$ Application Temp 0°C to $+40^{\circ}\text{C}$ Storage Temp $+12^{\circ}\text{C}$ to $+25^{\circ}\text{C}$



NOTE

Except where indicated otherwise, the above figures are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.







AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Advance Tapes International Limited, PO Box 122, Abbey Meadows, Leicester, LE4 5RA. Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com

^{*}Standard charge for certificate:£25.00.